



## Technical Specifications

**Product Line:** 20-2C-TTPSH

### Description

2 conductor 20 AWG stranded, twisted, and shielded cable

NEC type CMP and CEC type CMP FT6. Product manufactured compliant to the requirements of UL444 for installations and applications in accordance with NEC articles 725 and 800.

### Conductor

20 AWG

10-strand annealed bare copper conductors

Diameter: 0.0365" | 0.93mm

### Insulation

Plenum rated polyvinyl chloride

Wall thickness: 0.010" | 0.25mm

Diameter: 0.0565" | 1.435mm

### Color Code

Black, Red

### Assembly

2 conductors twisted

Lay length: 3.0" | 80mm

4.0 twists per foot | 12.5 twists per meter

### Construct

Ripcord under jacket

### Shield

100% aluminum/polyester tape foil out

24 AWG 7-strand tinned copper drain

### Jacket

Plenum rated polyvinyl chloride

Colors: Green

Wall thickness: 0.018" | 0.457mm

Diameter: 0.158" | 4.01mm

Specification Revision Date:

### Electrical

DC resistance: 10.50  $\Omega$  / 1000' | 34.44  $\Omega$ /KM

Mutual capacitance: 43.1 pF/FT | 141.36 pF/M

Impedance: 49  $\Omega$

Inductance: 0.15 $\mu$ H/FT | 0.49 $\mu$ H/M

Velocity of Propagation: 55%

Voltage rating: 300V

Maximum current: 3.75A@25°C

### Regulatory

NEC: CMP 60°C

CEC: CMP FT6 60°C

EU RoHS 2002/95/EC Compliant

### Packages

Reel: 1000' | 305M

Weight: 19 Lbs/1000' | 29 Kg/KM

### Installation

Pull Tension: 20 Lbs | 89 N

Bend radius: 1.58" | 41mm unloaded

Bend radius: 3.16" | 82mm loaded

Plenum cable should be conditioned at room temperature for 24 hours prior to installation and never installed below 32°F | 0°C ambient temperature

### Applications

Plenum general purpose use, security and low voltage power

Plenum commercial and residential line level audio

Plenum Class 2 and 3 power

### Performance

Line level audio to 100 feet

### Final Outside Diameter (inches)

0.158

April 29, 2009

