

VS-411UHD

4x1 4K60 4:2:0 HDMI Auto Switcher with Audio

| HDMI | 4K/60 UHD (4:2:0)

VS-411UHD is an automatic switcher for 4K@60Hz (4:2:0) HDMI and analog audio signals. VS-411UHD automatically switches one of four HDMI inputs to a predefined or last connected input whenever the currently active video signal is interrupted or whenever a higher-priority video signal is detected. They also support Kramer's Step-in over HDMI technology

FEATURES

Max. Data Rate - 8.91Gbps (2.97Gbps per graphic channel)

Max. Resolution - 4K@60Hz (4:2:0)

Step-In Over HDMI Technology

HDTV Compatible

Active Switching - Selectable manual or fast auto switching according to last connected or preset priority

Compliance - HDMI 1.4, HDCP and DVI 1.0

HDMI 1.4 Support - Deep Color, 3D, up to 7.1 uncompressed audio channels, ARC (supported on Input 1 only)

HDMI ARC De-embedding - From output to balanced stereo audio line, uncompressed

Automatic Video Input Detection & Selection

Auto Power Off - When no HDMI input for 10 seconds (selectable)

Selectable HDCP Switching

EDID Configuration Options

Default EDID

Contact Closure - For remote manual switching override

Audio Embedding/De-embedding

Stereo Analog Audio Input Per Port

Balanced Stereo Audio Output

Lock Button - To prevent tampering

Firmware Upgrade - Over RS-232, mini-USB

Software Support - Protocol 3000, EDID Designer, K-Upload via RS-232

Varied Control Options - Front panel buttons, contact closure, IR, RS-232 Protocol 3000

TECHNICAL SPECIFICATIONS

| | |
|--------------------------------|---|
| INPUTS: | 4 HDMI connectors, 4 unbalanced stereo audio on 3.5mm mini jacks |
| OUTPUTS: | 1 HDMI connector, 1 balanced stereo audio on 5-pin terminal block |
| PORTS: | 1 RS-232 on a 3-pin terminal block, 1 mini USB for programming |
| COMPLIANCE WITH HDMI STANDARD: | HDMI 1.4, Deep Color, 3D, ARC, up to 7.1 uncompressed audio channels, CEC |
| MAX DATA RATE: | 8.91Gbps (2.97Gbps per graphic channel) |
| SUPPORTED RESOLUTIONS: | Up to 4K x 2K, 4K@60Hz (4:2:0) |
| CONTROLS: | Front panel buttons, contact closure, IR, RS-232 Protocol 3000 |
| SOFTWARE SUPPORT: | Protocol 3000, EDID Designer, K-Upload |
| POWER CONSUMPTION: | 5V DC, 500mA |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F) |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F) |
| HUMIDITY: | 10% to 90%, RHL non-condensing |
| INCLUDED ACCESSORIES: | Power adapter, IR remote control |
| OPTIONS: | RK-1 19" rack adapter |